



EW040417

7/16 DIN Male to HN Female Between Series Adapter

Material

Length	1.725 in
Width	1.25 in
Body Angle	Straight

Connector 1

Connector Type	7/16 DIN Male
Impedance	50 Ohm
Interface Specification	MIL-C-39012
Inner Conductor	Gold Plated MIL-G-45204
Insulation	PTFE
Body	Brass (Nickel Plated QQ-N-290)
Coupling Nut	Brass (Nickel Plated QQ-N-290)
Mating Torque	221 to 265 in-lbs
Hex Size	32 mm

Connector 2

Connector Type	HN Female
Impedance	50 Ohm
Interface Specification	MIL-STD-348
Inner Conductor	Gold Plated MIL-G-45204
Insulation	PTFE
Outer Conductor	Brass (Nickel Plated QQ-N-290)

Product Description

At eWaveRF, we have RF & microwave coaxial adapters in-stock and ready to ship same-day from our Southern California headquarters. eWaveRF coaxial adapters are available in a variety of connector types including, but not limited to: 1.0/2.3, 1.85mm, 10-32, 2.4mm, 2.92mm, 3.5mm, 7/16 DIN, 7mm, BNC, BNC Twinax, C, F, HN, LC, MCX, MHV, MMCX, N, QMA, SC, SHV, SMA, SMB, SMP, SSMA, SSMB, SSMC, TNC, and UHF. eWaveRF coaxial adapters are offered in a variety of frequency ranges spanning from DC to 65 GHz.

Specifically, the EW040417 is an between series 50 ohm 7/16 DIN to 50 ohm HN straight RF adapter. The EW040417 50 ohm 7/16 DIN adapter is manufactured with nickel plated brass. The EW040417 is RoHS compliant and ships the same day as ordered.

Drawings

